



RESIDENTIAL UPGRADES

- Bringing High Scale Quality to Designer Bathrooms

COMMERCIAL PROJECTS

- The Choice of Many of the Finest Hotels, Resorts, and Condominium Complexes Around the World

**FRAMELESS
SHOWER DOOR
HARDWARE AND SUPPLIES**



C.R. LAURENCE COMPANY

crlaurence.com





Prima Series Hinge



Prima Hinges provide extra application possibilities. Their Top and Bottom Pivot style handles the weight of the door better than traditional "Side Mount" hinges, as well as allowing greater glass exposure, thus making for a more aesthetic enclosure. Prima Hinges can be mounted floor and ceiling, floor and wall, floor and fixed transom, floor and inline panel, or floor and header for enclosures not reaching the ceiling.



SPECIFICATIONS:

For Glass Thickness: 5/16" (8 mm) to 3/8" (10 mm) Tempered Safety Glass

Note: Senior Prima Hinges are Available for 1/2" (12 mm) Thick Glass. Junior Prima Hinges are Available for 1/4" (6 mm) Thick Glass.

Construction: Solid Brass

Hinge Swings: Full Rotation

Closing Type: Self-Centering When Within 15° of Closed Position

Glass Fabrication: Cut-Out Required

Finishes: Over 20 Stock Colors (Custom Finishes Also Available)

Includes: Gaskets, Screws, Glass Fabrication Details



Vienna Series Hinge



Cologne Series Hinge



The ideal hinges for wider and heavier doors, two hinges can accommodate up to a 36" wide door weighing up to 110 pounds, while three hinges can accommodate up to a 36" wide door up to 140 pounds. Two strategically placed steel pins allow the hinge to be used in a "mouse-ear" shaped cut-out, thus providing a non-slip safety feature. For those customers wishing to do a rectangular style cut-out, the two steel pins may be removed, allowing more adjustability.



SPECIFICATIONS:

For Glass Thickness: 3/8" (10 mm) to 1/2" (12 mm) Tempered Safety Glass

Construction: Solid Brass

Hinge Swings: 90° Outward and 90° Inward

Closing Type: Self-Centering When Within 15° of Closed Position

Glass Fabrication: Cut-Out Required

Finishes: Over 20 Stock Colors (Custom Finishes Also Available)

Includes: Gaskets, Screws, Glass Fabrication Details

CRL Offers Over 20 Varieties of Hinge Series to Accommodate 1/4" to 1/2" (6 mm to 12 mm) Thick Glass and Match Most Any Modern Bathroom Décor





Geneva Series Hinge

10824/CRL
BUYLINE 3068



Pinnacle Series Hinge



Geneva Hinges offer three varieties of Wall Mount Hinges, in addition to three Glass-to-Glass models. Pinnacle Hinges offer two styles of Wall Mount Hinges, as well as three Glass-to-Glass models. Adjustable models (not pictured here) that feature up to 90° adjustment to accommodate "off angles" are also available.



SPECIFICATIONS:

For Glass Thickness: 3/8" (10 mm) to 1/2" (12 mm)
Tempered Safety Glass

Construction: Solid Brass

Hinge Swings: 90° Outward and 90° Inward

Closing Type: Self-Centering When Within 15° of Closed Position

Glass Fabrication: Cut-Out Required

Finishes: Over 20 Stock Colors (Custom Finishes Also Available)

Includes: Gaskets, Screws, Glass Fabrication Details



Regal Series Adjustable Hinge

Allen Adjustment Screw



Wall Mount



Glass-to-Glass
Shown in 180° Position



Glass-to-Glass
Shown in 135° Position



Glass-to-Glass
Shown in 90° Position

The Regal Hinge offers an adjustable closing angle from 0° to 90°. After the door is installed, simply loosen the Allen screw adjustment, position the door to the desired closed position, and tighten the Allen screw. You have now solved the problem of walls not meeting the door at the perfect 90° angle. This adjustment feature means that a single Glass-to-Glass model can accommodate angles from 90° to 180°.



SPECIFICATIONS:

For Glass Thickness: 5/16" (8 mm) to 3/8" (10 mm)
Tempered Safety Glass

Construction: Solid Brass

Hinge Swings: Approximately 90° Outward Only

Closing Type: Precise Closing to 0°

No Cut-out; Requires Two Holes Only Per Glass Panel.

Finishes: Up to Nine Stock Colors (Custom Finishes Also Available)

Includes: Gaskets, Screws and Glass Fabrication Dimensions

*A Full Line of Accessories
Provide the Finishing Touch
to Complement Your
Choice of Hinges and Design*

Jamb Mounted Hinge Kits, Pull Handles, Towel Bars, Knobs, Glass Clamps, U-Channel, Headers, Thresholds, Vanity Mirrors, Polycarbonate and Vinyl Wipes and Seals



Madrid Series Hinge

NEW!

- Our First Series of Frameless Shower Door Hinges That Are Notch-Free
- Fits 3/8" (10 mm) Glass with No Glass Fabrication Required (No Holes, No Cut-Outs)
- Three Mounting Options for Installation Versatility - Header Mount - Wall Mount - Soffit Mount



SPECIFICATIONS:

For Glass Thickness: 3/8" Tempered Safety Glass
Construction: Solid Brass
Hinge Swings: Full Rotation
Closing Type: Precise Closing to Zero Degrees
Glass Fabrication: Cut-Out Required
Finishes: Five Stock Colors (Custom Finishes Also Available)
Includes: Gaskets and Mounting Hardware



Arctic Series Hinge

NEW!

- Our Most Unique Design for the Construction of Frameless Showers
- Just Two Models Will Handle All of Your Glass-to-Glass and Glass-to-Wall Mounting Needs
- Set Doors at 90, 135, 180 Degrees, or Anywhere In-Between
- Constructed of Stainless Steel in Your Choice of Brushed or Polished Finishes
- Fits 5/16" (8 mm) and 3/8" (10 mm) Thick Glass (Holes Required)



SPECIFICATIONS:

For Glass Thickness: 5/16" (8 mm) to 3/8" (10 mm) Tempered Safety Glass
Special Features: Doors can be set at 90°, 135°, 180°, or anywhere in-between
Construction: Stainless Steel
Hinge Swings: Up to 180° Rotation
Closing Type: Free Swinging
Glass Fabrication: Two 1/2" (12 mm) Diameter Holes Required per Glass Panel
Finishes: Two Stock Finishes
Includes: Gasket, Screws (Glass-to-Wall Model), and Glass Fabrication Dimensions



Frameless Sliding Shower Door Kits

- Designed for 1/4" (6 mm) and 3/8" (10 mm) Glass
- Top Hung Design Allows for Bottom Track and Side Jamb to Remain Uncluttered
- Two Stock Sizes: 60" x 60" or 60" x 72"
- Custom Units Available

SPECIFICATIONS:

Materials: Extrusions (Aluminum), Towel Bar (Brass Tubing), Knob (Solid Brass)
For Glass Thickness: 1/4" (6 mm) and 3/8" (10 mm) (Glass not included in Kit)
Finishes: Three Stock Colors
Includes: Aluminum Extrusions, 24" (610 mm) Towel Bar, Knob, Hardware Package and Installation Instructions
Glass Fabrication: Towel Bar - Two 1/2" (12 mm) Diameter Holes, 24" (610 mm) Center-to-Center; Knob - One 1/2" (12 mm) Diameter Hole; Top Hangers - Four 1/2" (12 mm) Diameter Holes (two per glass panel)



NEW!

Literature to Add to Your Library

- A Full Line Catalog Complete with Product Specifications
- Over 100 Photographs of Beautifully Finished Shower Enclosures
- Allows Your Customers to Visualize Their New Shower Enclosures

GET YOUR FREE COPY TODAY!



Cat. No. SD05

Visit The World of crlaurence.com

- Access to All CRL Products Through Our Easy-to-Use A to Z Product Index
- New CRL Products and Services
- Technical Articles and Product Support
- Ordering and Shipping Information
- Help in Using the Site
- CRL Locations with Addresses, Directions, Phone and Fax Numbers
- Direct E-Mail Connections to CRL Departments



- A Calendar of Industry Trade Shows
- And Much More!

Technical Sales

For All Your Project Requirements



C.R. Laurence Company has a Technical Sales Department to assist with design plans and installation questions concerning Shower Door Hardware. Your job can be made easier with the help of our Technical Sales Representatives who are trained in the newest Hardware Systems, and can offer you detailed diagrams and layout sheets.

Ask for Extension 7740

Architectural Service

Designed for Architects

Ask for Extension 5272



Please visit us at crlaurence.com and click on the word "Architects". An Architectural Services area has been designed to allow you to review the product group of your choice. In addition, many product details and specifications are available. As always, you may request our detailed specialty catalogs such as Door Controls, Architectural Hardware, Railings Systems, Frameless Shower Door Hardware and Supplies, or Transaction Hardware.

SWEETS 05-SD



Request Your FREE Copy of Our CD-ROM that Includes All of Our Specialty Catalogs

crlaurence.com • (800) 421-6144 • Fax (800) 262-3299

