

CRL DESIGN CENTER

New Products + Special Design Criteria =
New Looks for Frameless Shower Door Installations

NEW!

HEADER-FREE SHOWER ENCLOSURE SYSTEM




Typical Header-Free Design
(Glass Not Included)

- Must Utilize CRL Established Criteria Below for Installing Safe Enclosure
- Choose Your Own Set of Current CRL Stock Products to Install, As Long As Criteria Is Followed
- Provides The "Frameless" Alternative Many Customers Demand

Header-Free Enclosure Criteria

- Must Use 1/2" (12 mm) Glass on Fixed Panel From Which the Door Hinges
- Fixed Panel From Which the Door Hinges Can't Exceed 22" (559 mm) in Width or 84" (2.13 m) in Height
- Door Can be Either 3/8" (10 mm) or 1/2" (12 mm) Glass
- Door Width Not to Exceed 30" (762 mm)
- Must Use One Type of the Following Brackets Fastened to the Vertical Wall on the Fixed Panel From Which the Door Hinges: GE90S, P190S, R090S or CA90S
- The Some Number of Brackets Will be Used on the Wall as There are Glass-to-Glass Hinges
- Only a Fixed Panel Fastened to a Vertical Wall can be Used to Hinge From. No Hinging From a Fixed Panel Fastened to Another Fixed Panel
- Fixed Panel From Which the Door Hinges Must Have Valid Bottom Support (Doesn't Have to be Same as Bracket Nated Above)



See
crlaurence.com
for Complete
Guidelines and
Approved Design
Criteria

CRL 3-POINT CEILING MOUNT MOVABLE TRANSOM CLAMP



Cat. No. GTC037
SQUARE CORNERS



Cat. No. PTC037
BEVELED EDGES



NEW!

- Mounts to Ceiling Instead of Traditional Side Mounting Application
- Three Stopping Points Include 45 Degrees Out, Closed Position, and 45 Degrees In
- Models to Match our Popular Geneva, Pinnacle, Vienna, and Cologne Hinge Series
- Stocked in Five Finishes for Use with 5/16", 3/8", and 1/2" (8 mm, 10 mm, and 12 mm) Thick Tempered Glass

SPECIFICATIONS:

Glass Thickness:
5/16" (8 mm) to 1/2" (12 mm) Tempered Safety Glass
Construction: Solid Brass
Cut-Out Required
Includes: Gaskets, Screws, and Glass Fabrication Dimensions

Our new 3-Point Ceiling Mount Movable Transom Clamp provides design alternatives to the traditional side mounted "teeter-totter" application. Mounted to the ceiling instead of the sides of the transom, allows a look preferred by many designers and customers. The Clamp will open 45 degrees inward, stay at the closed position, or open 45 degrees outward. The square and beveled appearance matches many popular CRL Hinge Series such as Geneva, Pinnacle, Vienna, and Cologne. Stocked in five popular finishes.

C.R. LAURENCE COMPANY | crlaurence.com

PHONE: (800) 421-6144 Ex1. 7740

FAX: (800) 458-7496

EMAIL: showers@crlaurence.com



CRL DESIGN CENTER

New Products + Special Design Criteria =
New Looks for Frameless Shower Door Installations

NEW!

CRL TOP OR BOTTOM MOUNT PIVOT HINGE WITH ATTACHED U-CLAMP

Cardiff Series

For 3/8" and 5/16" (8 mm and 10 mm) Glass



Cat. No. CAR07

Prima Series

For 3/8" and 5/16" (8 mm and 10 mm) Glass



Cat. No. PPH07

Senior Prima Series

For 1/2" (12 mm) Glass



Cat. No. SRPPH07

- Provides Alternative to Using Traditional Horizontal Metal Header Systems Across Enclosure
- CRL Engineered Design Criteria Must Be Followed for Safe Installation
- Typically Used With Standard "01 Model" Pivot Hinge At Bottom of Door
- Can Also Be Mounted at Bottom of Door and Adjacent Panel for Symmetry
- Stocked in Eight Popular Finishes, with Custom Finishes Available
- Models for 5/16", 3/8", and 1/2" (8, 10, 12 mm) Thick Tempered Glass

New Top and Bottom Pivot Hinges with Attached U-Clamp answer the question that many architects, designers, and customers have asked. "Do I have to have a Header on my beautiful new Shower Enclosure"? Well, sometimes the answer may be yes, but carefully following CRL engineered design criteria for these hinges may allow you this alternative appearance. This combination of Hinge and U-Clamp at the top allows the installer to mount a shower door next to an adjacent 180 degree fixed panel without a Header. The same look may be done at the bottom of the door and fixed panel, or a Standard "01 Model" Bottom Mount Pivot Hinge may be used with other clamps or U-channel. Stocked in eight popular finishes, with custom finishes available. Models available for 5/16", 3/8", and 1/2" (8, 10, and 12 mm) thick tempered glass.



SPECIFICATIONS:

Glass Thickness:

Prima and Cardiff 5/16" and 3/8" (8 mm and 10 mm)
Tempered Safety Glass

Senior Prima 1/2" (12 mm) Tempered Safety Glass

Construction: Solid Brass

Hinge Swings: Full Rotation

Closing Type: Self-Centering when within 15°
of closed position

Cut-Out Required

Includes: Gaskets, Screws, and Glass
Fabrication Dimensions

See
crlaurence.com
for Complete
Guidelines and
Approved Design
Criteria

AVDB4039-9/10



C.R. LAURENCE COMPANY | crlaurence.com

PHONE: (800) 421-6144 Ext. 7740

FAX: (800) 458-7496

EMAIL: showers@crlaurence.com

