


EXCLUSIVELY DESIGNED, ENGINEERED AND MANUFACTURED BY C.R. LAURENCE CO.

GLASS ENTRANCE SYSTEM

A TOTALLY NEW CONCEPT Wedge-Lock Dry Glazed Door Rail System

The Fastest and Easiest Way to Secure
Glass in Commercial Door Rails

- Exclusive CRL Wedge-Lock Glass Securing System for Rapid Installation and Steadfast Holding Power
- Solid Aluminum Rail, Rigid Single Component Housing Will Not Shift and Fall Out of Adjustment Over Time Because the Housing is Not Made Up of Two Halves
- Door Assembly Can Be Ready for Installation in Less Than 10 Minutes
- Universal Top and Bottom Rails Cut Inventory in Half and Make Ordering Easier
- Dry Glazing Allows Easy Field Glass Replacement
- Available With or Without a Lock
- Locks are Easily Changed Out
- Adjustable Door Alignment System Allows Jamb Line Adjustment Without Removing the Door
- Internal Components Do Not Require Removal Before Installation
- Glass Securing Pads Designed for Longevity in Extreme Environments
- Factory Applied Cladding
- Pull Tested to Over 7,000 lbs. (Slipped but Didn't Fail)
- Five Stock Finishes in Single Door and Double Door Styles Available in 4", 6" and 10" Heights. Custom Sizes and Finishes Also Available



WEDGE-LOCK GLASS SECURING SYSTEM Patent Number 6,434,905

The patented Wedge-Lock Glass Securing System is a totally new concept for securing the glass in the Door Rail.

Tempered bolts draw the tapered clamp jaws downward against the internal wedge design of the rail body, resulting in very high gripping pressure along the entire edge of glass. The solid aluminum rail provides full support for bonded cladding, resulting in perfectly smooth appearance and trouble free service life.

CRL Panic, Deadbolt and Electronic Egress Handles

- Available in Polished or Brushed Stainless Steel
- Can Be Used as a Replacement for Older Panics
- Dogging Feature Defeats Locking Action During Business Hours
- Custom Sizes Ship Within Two Weeks

New CRL Glass Door Panic and Deadbolt Handles are designed to allow maximum view and a contemporary look to 1/2" or 3/4" tempered glass doors. Installations can be made on single or double doors. They are ready to be installed on 36" to 48" wide doors ranging from 90" to 102" high without modifications. "Dogging", locking the device in the open position, is easy with just a slide of a knob. Available through local temperers or glass fabricators.

CRL ISO 9000 Certified Company
C.R. LAURENCE CO., INC.

Glazing, Industrial, Construction and Automotive Supplies

Phone: (800) 421-6144 • Fax: (800) 587-7501 • Website: www.crlaurence.com • E-Mail: techsales@crlaurence.com



WEDGE-LOCK & FRAMELESS SHOWER DOOR RAIL SYSTEM DOOR HARDWARE

Fast, Secure Attachment to the Glass is Easy with Wedge-Lock Design Rails

Covering the Entire Spectrum of Doors with 4", 6" and 10" Rails in Five Beautiful Stock Finishes



The Unique Wedge-Lock Clamps the Glass Securely, yet Removes Easily



Mfr. Patent No. 6,434,905

The new Wedge-Lock Door Rail System provides the fastest fabrication and installation. Experienced installers can now secure a door rail in less than ten minutes. After rail installation to the glass, all that is needed before hanging the door is attachment of the appropriate arm or pivot to the unique, pre-installed adjustable slide-block. This standard feature on both top and bottom rails allows for door alignment without removing the door.

Wedge-Lock Securing Door Rails are available in five stock finishes in single and double door styles, and accept 3/8" (10 mm) or 1/2" (12 mm) glass. By using the new Wedge-Lock Door Rail System glass professionals can simplify the ordering process, cut inventory in half, and speed the installation process.

Tempered bolts draw the tapered clamp jaws downward against the internal wedge design of the rail body, resulting in very high gripping pressure along the entire edge of the glass. *National Technical Systems tested the Wedge-Lock Door Rail System at a temperature range from -10°F to 150°F, with 1000 pounds of tension load applied. No evidence of movement was detected at any temperature. At 75°F ambient temperature, in a "Pull-To-Failure Test", nearly 7000 pounds of tension was required before any creep (not failure) was detected.

*Certified Laboratory

Durable, High Quality Frameless Shower Door Hardware and Fixtures

- Hinges
- Knobs
- Latches
- Pull Handles
- Towel Bars
- Glass Clamps
- Wall Brackets
- Accessories

We can now take care of all your frameless shower door and heavy glass commercial door needs.

Just give us the opening, and in one stop we will do all the necessary calculations to accurately supply your glass and hardware.



NO MORE WAITING

When your glass is ready... everything you need for your installation comes in one complete package.



1 General Motors Drive
Syracuse, NY 13207

Phone: (315) 437-9971
Fax: (315) 437-8118

(800) 962-3211
syracuseglass.com