



OPACI-COAT 300 SPANDREL GLASS

QUOTE REQUEST

ORDER FORM PO # _____

Customer Name: _____

Customer Contact: _____

Job Name: _____

OPACI-COAT Color Name/Number: _____

Color is: () Stock Color **OR** () Custom Color
() Dark Color **OR** () Light, White, or Pastel Color

Fallout Protection () Not Required () Required

Heat Treating Required: () Tempered () Heat Strengthened

Logos Required: () Yes () No

MONOLITHIC OPACI-COAT
Glass Substrate:
() 1/4" Clear
() Other _____

OR

INSULATING OPACI-COAT
Glass Substrate: Outboard _____
Inboard _____
Coating On: () #2 Surface
() #4 Surface
Secondary Seal: () Polysulfide
() Silicone - Required
for Structural Glazing

For Monolithic and #4 Surface Insulating:

Glazing System: () Conventional
() Two-2-Sided Structural () Glazed with Dow 995
() Edge Deleted Vertical
() Edge Deleted Horizontal

Monolithic and #4 Surface OPACI-Coat 300 NOT RECOMMENDED for Four-Sided Structural Glazing.

Are gaskets, sealants, setting blocks compatible, or should we apply bond breaker tape around perimeter or coated surface?

(Neoprene is not compatible) () No Tape
() Apply Tape

OPACI-COAT 300 is intended for building spandrel areas, (not vision area) backed up with another building material.

NOTES: _____

Attach Sizes and Quantities. Fax to: 315-437-8118